

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name & Synonyms : LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

General Use : Polyamide for automotive parts, mechanical parts, electric and electronic parts.
Product Description : Polyamide 66, Polyamide 66/6I, Polyamide 66/6, Polyamide 6
MSDS Number : LE-A002-02

MANUFACTURER

Company Name : Asahi Kasei Chemicals Corporation
Address : Performance Plastics Division
1-105 Kanda Jinbocho, Chiyoda-ku, Tokyo 101-8101 Japan

Importer/Distributor Established in U.S.A
Asahi Kasei Plastics North America, Inc.
900 E. Van Riper Rd., Fowlerville, MI 48836, U.S.A

EMERGENCY TELEPHONE NUMBER:

CHEMTREC

United States : (800)-424-9300 24 hours Everyday
International : +1-(703)-527-3887 (Collect) 24 hours Everyday


NONTRANSPORTATION

Asahi Kasei Plastics North America, Inc.
+1-(517)-223-0000 9am – 6pm ET M-F
Asahi Kasei Chemicals Corporation
+81-(44)-271-2417 (Performance Plastics Development Dept.)
9am – 6pm Japan Time M-F

2. COMPOSITION/INFORMATION ON INGREDIENTS

Product Name: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR380, TR161, TR382, SR100, 1300L, 1300SL, LC010, LC020, LC025, LC030, LC050, LC060

Chemical Formula (main ingredient):



Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

Product Name	Chemical Name	Wt%	CAS Registry No.
13G15, 14G15	Polyhexamethylene adipamide	80 - 90	32131-17-2
	Glass fiber	10 - 20	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
13G23, 13G25, 14G23, 14G25	Polyhexamethylene adipamide	70 - 80	32131-17-2
	Glass fiber	20 - 30	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
13G30, 13G33, 1300G 14G30, 14G33, 1402G 1402GH	Polyhexamethylene adipamide	63 - 73	32131-17-2
	Glass fiber	27 - 37	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
13G43, 14G43	Polyhexamethylene adipamide	52 - 62	32131-17-2
	Glass fiber	38 - 48	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
13G50, 14G50	Polyhexamethylene adipamide	45 - 55	32131-17-2
	Glass fiber	45 - 55	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
CR301	Polyhexamethylene adipamide	55 - 65	32131-17-2
	Talc / Kaolin	35 - 45	14807-96-6 / 1332-58-7
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
CR302	Polyhexamethylene adipamide	50 - 60	32131-17-2
	Glass fiber	15 - 25	65997-17-3
	Talc / Kaolin	20 - 30	14807-96-6 / 1332-58-7
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
CR101	Polyhexamethylene adipamide	50 - 60	32131-17-2
	Glass fiber	5 - 15	65997-17-3
	Kaolin	20 - 30	1332-58-7
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
MR001	Polyhexamethylene adipamide	55 - 65	32131-17-2
	Wollastonite	35 - 45	13983-17-0
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
CR103	Polyhexamethylene adipamide	50 - 60	32131-17-2
	Glass fiber	5 - 15	65997-17-3
	Wollastonite	20 - 30	13983-17-0
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

13N05, 94N05, 17N05	Polyhexamethylene adipamide	90 - 99	32131-17-2
	Inorganic filler	1 - 10	On TSCA Inventory
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
5300G, 53G33	Polyhexamethylene adipamide	30 - 40	32131-17-2
	Other type of polyamide	23 - 38	On TSCA Inventory
	Glass fiber	28 - 38	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
54G33, 54G43	Polyhexamethylene adipamide	35 - 50	32131-17-2
	Other type of polyamide	10 - 25	On TSCA Inventory
	Glass fiber	28 - 48	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
5RG33	Polyhexamethylene adipamide	40 - 50	32131-17-2
	Other type of polyamide	15 - 25	On TSCA Inventory
	Glass fiber	28 - 38	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
TR160, TR380 TR161, TR382	Polyhexamethylene adipamide	70 - 95	32131-17-2
	Elastomers	5 - 30	On TSCA Inventory
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
SR100	Polyhexamethylene adipamide	60 - 80	32131-17-2
	Elastomers	5 - 15	On TSCA Inventory
	Kaolin	15 - 25	1332-58-7
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
1300L, 1300SL, LC010, LC020, LC025, LC030, LC050, LC060	Polyhexamethylene adipamide	65 - 99	32131-17-2
	Pigments	1 - 35	On TSCA Inventory
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	

Glass Fiber dust is the hazardous ingredient by definition of definition of Hazard Communication Standard.


* Light-Stabilizer, heat-stabilizer, Lubricant, colorant, etc. are added, in some grades. These additives except Carbon Black (CAS No. 133-86-4) and Titanium Dioxide (CAS No. 13463-67-7) are not hazardous by definition of Hazard Communication Standard. Carbon Black and Titanium Dioxide are hazardous ones.

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

Product Name: LEONA 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 8000L, 8002L

Chemical Formula (main ingredient):



Product Name	Chemical Name	Wt%	CAS Registry No.
90G33	Polyhexamethylene adipamide/ Polyhexamethylene isophthalamide copolymer	63 - 73	26353-66-2
	Glass fiber	27 - 37	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
90G50, 90G55, 90G60	Polyhexamethylene adipamide/ Polyhexamethylene isophthalamide copolymer	35 - 55	26353-66-2
	Glass fiber	45 - 65	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
91G40	Polyhexamethylene adipamide/ Polyhexamethylene isophthalamide copolymer	58 - 68	26353-66-2
	Glass fiber	5 - 15	65997-17-3
	Kaolin	22 - 32	1332-58-7
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
CR701	Polyhexamethylene adipamide/ Polyhexamethylene isophthalamide copolymer	55 - 65	26353-66-2
	Glass fiber	15 - 25	65997-17-3
	Talc	15 - 25	14807-96-6
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
800L, 8002L	Polyhexamethylene adipamide/ Polyhexamethylene isophthalamide copolymer	60 - 70	26353-66-2
	Pigments	30 - 40	On TSCA Inventory
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	

Glass Fiber dust is the hazardous ingredient by definition of definition of Hazard Communication Standard.


Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

*Light-Stabilizer, heat-stabilizer, Lubricant, colorant, etc. are added, in some grades. These additives except Carbon Black (CAS No. 133-86-4) and Titanium Dioxide (CAS No. 13463-67-7) are not hazardous by definition of Hazard Communication Standard. Carbon Black and Titanium Dioxide are hazardous components.

Product Name: LEONA 93G22, 93G33, WG143, WG145

Chemical Formula (main ingredient):




Product Name	Chemical Name	Wt%	CAS Registry No.
93G22, 93G33	Polyhexamethylene adipamide/ Poly-ε-caprolactamamide copolymer	28 - 38	24993-04-2
	Other type of Polyamide	20 - 30	On TSCA Inventory
	Glass fiber	17 - 38	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	
WG143, WG145	Polyhexamethylene adipamide/ Poly-ε-caprolactamamide copolymer	15 - 45	24993-04-2
	Other type of Polyamide	20 - 40	On TSCA Inventory
	Glass fiber	28 - 60	65997-17-3
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	

Glass Fiber dust is the hazardous ingredient by definition of definition of Hazard Communication Standard.

* Light-Stabilizer, heat-stabilizer, Lubricant, colorant, etc. are added, in some grades. These additives except Carbon Black (CAS No. 133-86-4) and Titanium Dioxide (CAS No. 13463-67-7) are not hazardous by definition of Hazard Communication Standard. Carbon Black and Titanium Dioxide are hazardous components.

Product Name: LEONA 2300L

Chemical Formula (main ingredient):



Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

Product Name	Chemical Name	Wt%	CAS Registry No.
2300L	Poly-ε-caprolactamamide	55 - 99	25038-54-4
	Pigments	1 - 45	On TSCA Inventory
	Other Additives*	0 - 3	On TSCA Inventory
	Total	100	

* Light-Stabilizer, heat-stabilizer, Lubricant, colorant, etc. are added, in some grades. These additives except Carbon Black (CAS No. 133-86-4) and Titanium Dioxide (CAS No. 13463-67-7) are not hazardous by definition of Hazard Communication Standard. Carbon Black and Titanium Dioxide are hazardous components.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Solid pellet has slight or no odor. Spilled pellets create slipping hazard. Product may be flammable when exposed to contact flame or heat sources. When product burns, it creates dense toxic vapors, gases or fumes.

Note: Fumes produced during melt processing may cause eye, skin and respiratory tract irritation. Operations such as grinding, sanding or sawing, can produce dust which might cause an explosion or respiratory hazard.

POTENTIAL HEALTH EFFECTS:

Inhalation: Pellets inhalation unlikely due to physical form

Inhalation of gas from molten resin may cause nausea.

Eye: Pellets may cause irritation or injury due to mechanical action

Skin: Pellets not likely to cause skin irritation

Contact with molten resin causes thermal burn.

Ingestion: Oral toxicity data is not established.

Small amount of swallowed incidentally during normal handling operations are not likely to cause injury; however, swallowing large amount may cause injury. Not acutely toxic.

Note: Carbon black, is added in some grades, is listed by Group 2B of IARC Cancer Review.

See 11. TOXICOLOGICAL INFORMATION

Certain sensitive materials or ingredients and individuals with respiratory impairments may be affected by exposure to components in processing fumes.

POTENTIAL ENVIRONMENTAL EFFECTS

Additives containing certain heavy metal compounds may present. These ingredients are encapsulated in the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

4. FIRST AID MEASURES

INHALATION: If inhalation of gas from molten resin causes nausea, remove the individual to fresh air and keep him at rest for recovery. If his condition does not improve, seek medical attention.

If inhalation of processing fumes causes irritation, leave contaminated area and breath fresh

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

air. If coughing, difficult breathing or any other symptoms develop, seek medical attention at once, even if symptoms develop at later time.

EYE: If the material is in a molten state, immediately cool and wash with clean water for at least 15 minutes. Remove contact lenses immediately if worn, unless they have adhered to eyes, and seek immediate medical attention.

SKIN: If the material is in a molten state, cool with clean water immediately. Do not forcibly remove any solidified resin stuck to the skin, but continue cooling until it becomes readily removable. Get medical attention for thermal burn. For skin contact with fume condensate, immediately wash affected area thoroughly with soap and water. If irritation develops, seek medical attention.

INGESTION: Induce vomiting only if the victim is conscious. In case of heavy ingestion, seek medical attention.

PROTECTION TO FIRST-AIDERS: Not applicable

NOTE TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Flash Point : Not applicable
Lower flammable limit : Not established
Upper flammable limit : Not established
Auto-ignition Temperature: ≥ 400 deg. C (≥ 725 deg. F)

EXTINGUISHING MEDIA:

Water spray and foam. Water is the best extinguishing media. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition.

FIRE FIGHTING INSTRUCTIONS:

Approved pressure demand breathing apparatus and protective clothing should be used for all fires. Water spray is a preferred extinguishing media. This material will melt but will not be carried on the surface of water.

HAZARDOUS COMBUSTION PRODUCTS:

Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide, a trace of HCN and NH₃.

6. ACCIDENTAL RELEASE MEASURES

LAND SPILL: Spills over road or floor may cause slipping and falling; spilt pellets should be collected and disposed properly. (Method of disposal must be in compliance with 13. DISPOSAL CONSIDERATIONS)

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

WATER SPILL: spilt pellets should be collected and disposed properly. (Method of disposal must be in compliance with 13. DISPOSAL CONSIDERATIONS)

7. HANDLING AND STORAGE

HANDLING: Should process this product under the recommended temperature range.

Do not inhale gas during processing of the material.

Do not hold the material at high temperature over an extended time.

STORAGE: Store in dry place, away from excessive heat and ignition sources.

Avoid direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMIT VALUES:

Particulates not otherwise classified

OSHA PEL	: 15 mg/m ³ (Total Dust) 5 mg/m ³ (Respirable fraction)
ACGIH TLV-TWA (2006)	: 10 mg/m ³ (Inhalable particulate) 3 mg/m ³ (Respirable particulate)

Synthetic vitreous fibers

Continuous filaments glass fibers

OSHA PEL	: Not established
ACGIH TLV-TWA (2006)	: 5 mg/m ³ (Inhalable fraction)

Talc (containing no asbestos)

OSHA PEL	: 20 millions of particles per cubic foot of air, based on impinger samples counted by light-filed techniques (Containing less than 1 % quartz; if 1% quartz or more, use quartz limit.)
ACGIH TLV-TWA (2006)	: 2 mg/m ³ (Respirable fraction)

Carbon Black

OSHA PEL	: 3.5 mg/m ³
ACGIH TLV-TWA (2006)	: 3.5 mg/m ³

Titanium dioxide

OSHA PEL	: 15 mg/m ³ (Total Dust)
ACGIH TLV-TWA (2006)	: 10 mg/m ³

EXPOSURE CONTROLS

Occupational Exposure Controls

Engineering controls: In case where possibilities of dust formation, gas generation or vapor emission exist, provide local ventilation. Ventilation requirements must be locally determined to

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

minimize exposure to materials at their point of use.

Personal Protection

Respiratory Protection: When processing fumes are not adequately controlled, use appropriate mask for protection from organic vapors and acid gases. When dust or powder from secondary operation, such as grinding, sanding or sawing, are not adequately controlled, use appropriate respirator for protection from dust.

Skin/Hand Protection : When handling pellets, avoid prolonged or repeated contact with skin. During processing, wear long pants, long sleeves, well insulated gloves and face shield. Use appropriate protective clothing, including chemical resistance gloves to prevent any contact with processing fume condensates.

Eye Protection : Wear safety glasses or chemical goggles while using or handling this material.

Environmental Exposure Controls

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Solid (Pellet shape)
Odor : Slight odor
pH : Not applicable
Boiling Point/Boiling Range : Not applicable
Melting Point/Melting Range : 215 – 270 deg. C (401 – 518 deg. F)
Decomposition Temperature : above 300 deg. C (572 deg. F)
Flash Point : above 400 deg. C (752 deg. F)
Auto Ignition Temperature: above 400 deg. C (752 deg. F)
Flammability : Flammable
Explosive Properties : Potential dust explosion may exist.
Oxidizing Properties : Stable at normal temperature

Vapor Pressure : Not applicable
Specific gravity : 1.1 – 1.8 g/cm³
Solubility : Insoluble in water

10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Temperature above 340 deg. C (644 deg. F)

In order to avoid auto-ignition / hazardous decomposition of heat thick masses

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

of plastic, purgings should be collected in small, flat shapes or thin strands to allow for rapid cooling in water.

STABILITY: Stable at normal temperature.

MATERIALS TO AVOID: Incompatible or can react with strong acids, oxidizing agents.

HAZARDOUS REACTIONS/DECOMPOSITION PRODUCTS:

When ignited, hazardous vapors can be released, including carbon monoxide, carbon dioxide, ammonia, hydrogen cyanide, nitrogen oxide.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity: Not available

Eye Irritation: Not considered primary eye irritant

Skin Irritation: Not considered primary skin irritant

Sensitization: Not considered primary skin irritant

Chronic Toxicity: Not available

Mutagenicity: Not available

Carcinogenicity: Carbon Black is listed by Group 2B of IARC Cancer Review and Titanium dioxide is listed by Group 3 of IARC Cancer Review

12. ECOLOGICAL INFORMATION

No information is available. Do not dump or discharge into ocean or any body of water, to avoid ingestion by marine life or birds.

13. DISPOSAL CONSIDERATIONS

Comply with all federal, state and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

14. TRANSPORT INFORMATION:

Not regulated in transportation by DOT/IMO/IATA

Note: Avoid water and careless handling to prevent damage of the container.

15. REGULATORY INFORMATION

OSHA STATUS: Hazardous under OSHA hazardous communication standard 29 CFR 1910.1200.

TSCA STATUS: on TSCA inventory

CERCLA REPORTABLE QUANTITY (40CFR117.302) : Not established

SARA TITLE III

SECTION 302 (40 CFR 355) : None

SECTION 311/312 (40 CFR 370) : Not hazardous

SECTION 313 (40 CFR 372) : None

Please refer to any other federal, state and local regulations.

Product: LEONA 13G15, 13G23, 13G25, 13G30, 13G33, 1300G, 13G43, 13G50, 14G15, 14G23, 14G25, 14G30, 14G33, 1402G, 1402GH, 14G43, 14G50, CR301, CR302, CR101, MR001, CR103, 13N05, 94N05, 17N05, 90G33, 90G50, 90G55, 90G60, 91G40, 91G55, 91G60, CR701, 93G22, 93G33, WG143, 5300G, 53G33, 54G33, 54G43, 5RG33, TR160, TR161, TR380, TR382, SR100, 1300SL, 1300L, LC010, LC020, LC025, LC030, LC050, LC060, 2300L, 8000L, 8002L, WG145

MATERIAL SAFETY DATA SHEET

16. OTHER INFORMATION

<Notice & Warning>

Do not use for the parts below.

- Medical vessels, packages, apparatus, parts which touch inside the human body, mucous membranes, body fluid, blood, and medicine
- Containers, packages, and parts for food applications
- Apparatus, parts which contact drinking water and beverages
- Toys which may be sucked or may contact drinking water and beverages

NOTE : The information furnished in this Material Safety Data Sheet is accurate to the best knowledge of Asahi Kasei Chemicals Corporation ("Asahi") as of the date of its publication. This MSDS is not intended to create any liability of any kind on the part of Asahi. In no event will Asahi be responsible for any death, injury or damage of any nature resulting from the use of, reliance upon, or misuse of the MSDS or material to which it refers. The data on this sheet relates only to the specific material designated herein.

No representations or warranties, whether express or implied, of merchantability, fitness for particular purpose, or any other nature, are made hereunder.

This MSDS is not intended as a recommendation for uses that infringe valid patents or extend licenses under valid patents. This MSDS is furnished under the express condition that all persons receiving it will make their own determination as to its suitability for their purpose prior to use.

Responsibility for compliance with applicable all national and local regulations concerning dissemination of the MSDS and sale and use of the material to which it refer rests solely upon the purchaser. For more information, please contact Asahi at the address and telephone number listed on this sheet.