

极速翻译

将当前网页翻译为:

中文(简体) ▼

极速引擎 更多专业引擎

翻译

引擎偏好设置

☐ 自动翻译此网站

Model KG-7330
File Number: E314830



COMPANY

FOSHAN SHUNDE KINGDE ENGINEERING PLASTICS CO LTD
Rd 1, Nanlang Industrial Zone
Xingtan
Shunde
Foshan, Guangdong 528326 China

MODEL INFO

KG-7330
Polyamide 66 (PA66), furnished as pellets

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
0.75 mm, Color: NC, BK	HB	
3.0 mm, Color: NC, BK	HB	
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
0.75 mm, Color: NC, BK	HB75	
3.0 mm, Color: NC, BK	HB40	
ELECTRICAL PROPERTIES	VALUE	TEST METHOD
Hot-wire Ignition (HWI)		UL 746A
0.75 mm	PLC 3	
3.0 mm	PLC 3	
High Amp Arc Ignition (HAI)		UL 746A
0.75 mm	PLC 0	

译

极速翻译

将当前网页翻译为:

极速引擎 更多专业引擎

引擎偏好设置

?

×

☐ 自动翻译此网站

Relative Thermal Index - Electrical Strength		UL 746B
0.75 mm	65 °C	
3.0 mm	65 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
0.75 mm	65 °C	
3.0 mm	65 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
0.75 mm	65 °C	
3.0 mm	65 °C	

Report Date: 2024-07-15
Revision Date: 2024-07-15

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

