

极速翻译

将当前网页翻译为:

中文(简体)

极速引擎 更多专业引擎

翻译

引擎偏好设置

☐ 自动翻译此网站

Model EXL1434T(GG)
File Number: E45329



COMPANY

SABIC INNOVATIVE PLASTICS B V
EUROPE - RESIN
PLASTICSLAAN 1
BERGEN OP ZOOM, 4612 PX Netherlands

MODEL INFO

EXL1434T(GG)
PC/Siloxane "Lexan, ELCRES", UV Stabilized, furnished as pellets
(GG) – Denotes a global grade formulation previously in File E161759.
NOTE – Material designation may be followed by a color nomenclature consisting of either an alpha/numeric or a numeric/alpha combination.

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
0.4 mm, Color: ALL	HB	
0.8 mm, Color: ALL	HB	
1.5 mm, Color: ALL	HB	
2.5 mm, Color: ALL	HB	
3.0 mm, Color: ALL	V-2	
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
0.4 mm, Color: ALL	HB75	
0.8 mm, Color: ALL	HB75	
1.5 mm, Color: ALL	HB75	
2.5 mm, Color: ALL	HB75	
3.0 mm, Color: ALL	V-2	

UL Solutions 的 Cookie

我们通过 Cookie 使内容和广告个性化，以便提供社交媒体功能并分析我们的流量。我们还与社交媒体、广告和分析合作伙伴来分享您使用网站的信息。 [了解更多](#)

Cookie 设置 拒绝全部 接受全部 Cookie

极速翻译

将当前网页翻译为:

极速引擎 更多专业引擎

引擎偏好设置

☐ 自动翻译此网站

0.8 mm	850 °C
1.5 mm	850 °C
2.5 mm	850 °C
3.0 mm	850 °C
Glow Wire Flammability Index (GWFI) IEC 60695-2-12	
0.4 mm	825 °C
0.8 mm	825 °C
1.5 mm	825 °C
2.5 mm	825 °C
3.0 mm	960 °C
THERMAL PROPERTIES	
VALUE	
TEST METHOD	
Relative Thermal Index - Electrical Strength UL 746B	
0.4 mm	80 °C
0.8 mm	80 °C
1.5 mm	130 °C
2.5 mm	130 °C
3.0 mm	130 °C
Relative Thermal Index - Mechanical Impact UL 746B	
0.4 mm	80 °C
0.8 mm	80 °C
1.5 mm	120 °C
2.5 mm	120 °C
3.0 mm	120 °C

Relative Thermal Index - Mechanical Strength UL 746B

UL Solutions 的 Cookie

我们通过 Cookie 使内容和广告个性化，以便提供社交媒体功能并分析我们的流量。我们还与社交媒体、广告和分析合作伙伴来分享您使用网站的信息。[了解更多](#)

0.4 mm 80 °C

0.8 mm 80 °C

1.5 mm 130 °C



将当前网页翻译为:

极速引擎 更多专业引擎

引擎偏好设置



☐ 自动翻译此网站

REVISION DATE: 2022-03-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."



UL Solutions 的 Cookie

我们通过 Cookie 使内容和广告个性化，以便提供社交媒体功能并分析我们的流量。我们还与社交媒体、广告和分析合作伙伴来分享您使用网站的信息。 [了解更多](#)