

iq.ul.com

PROSPECTOR®

CLICK TO CONTINUE

The information presented on the UL Prospector datasheet was acquired by UL Prospector from the producer of the material. UL Prospector makes substantial efforts to assure the accuracy of this data. However, UL Prospector assumes no responsibility for the data values and strongly encourages that upon final material selection, data points are validated with the material supplier.

View additional material information including performance and processing data

Component - Plastics

Guide Information

View Certificate of Compliance

E45329

SABIC INNOVATIVE PLASTICS B V

EUROPE - RESIN, PLASTICSLAAN 1, BERGEN OP ZOOM 4612 PX NL

420SE0(f1)(w)(GG)(rr2)

Polybutylene Terephthalate (PBT) "Valox", furnished as pellets

Color	Min. Thk (mm)	Flame Class	HWI	HA	RTI Elec (°C)	RTI Imp (°C)	RTI Str (°C)
ALL	0.75	V-0	3	0	130	130	140
	1.0	V-0	3	0	130	130	140
	1.5	V-0	2	0	130	130	140
	2.0	V-0, 5VA	2	0	130	130	140
	3.0	V-0, 5VA	0	0	130	130	140

Comparative Tracking Index (CTI): 3

Dielectric Strength (kV/mm): 27

High-Voltage Arc Tracking Rate (HVTR): 4

Dimensional Change (%): 0

Inclined Plane Tracking (IPT) kV: -

Volume Resistivity (10^x ohm-cm): 15

Surface Resistivity (10^x ohms/square): -

High Volt, Low Current Arc Resis (D495): 6

(GG) - Denotes a global grade formulation previously in File E161759.

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

(rr2) - Virgin and regrind up to 50% by weight inclusive

(w) - Recognition includes the use of surface dyes.

NOTE - Material designation may be followed by a color nomenclature consisting of either an alpha/numeric or a numeric/alpha combination.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1981-10-06

Last Revised: 2024-10-03

© 2025 UL Solutions



ALSO CERTIFIED TO IEC REQUIREMENTS

IEC and ISO Test Methods				
Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10, IEC 60695-11-20	Class (color)	0.75	V-0 (ALL)
			1.0	V-0 (ALL)
			1.5	V-0 (ALL)
			2.0	V-0, 5VA (ALL)
			3.0	V-0, 5VA (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	0.75	960
			1.0	960
			1.5	960
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	0.75	700
			1.0	700
			1.5	700
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	CTI175
IEC AC Dielectric Strength (AC DS)	IEC 60243-1	Material Group	-	IIIa
IEC DC Dielectric Strength (DC DS)	IEC 60243-2	kV/mm	-	-
IEC Volume Resistivity (VR)	IEC 62631-3-1	kV/mm	-	-
IEC Surface Resistivity (SR)	IEC 62631-3-2	10 ^x ohm-m	-	-
IEC Inclined Plane Tracking (IPT)	IEC 60587	10 ^x ohms	-	-
IEC Ball Pressure	IEC 60695-10-2	kV	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	175
ISO Tensile Strength	ISO 527-2	°C	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	MPa	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-1	kJ/m ²	-	-