

极速翻译

将当前网页翻译为:

中文(简体)

极速引擎 更多专业引擎

翻译

引擎偏好设置

☐ 自动翻译此网站

Model CX7240 (GG)(f2)
File Number: E45329



COMPANY

SABIC INNOVATIVE PLASTICS B V
EUROPE - RESIN
PLASTICSLAAN 1
BERGEN OP ZOOM, 4612 PX Netherlands

MODEL INFO

CX7240 (GG)(f2)
Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS) "Cycoloy, ELCRES", furnished as pellets
(GG) – Denotes a global grade formulation previously in File E161759.
(f2) – Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.
NOTE – Material designation may be followed by a color nomenclature consisting of either an alpha/numeric or a numeric/alpha combination.

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
0.75 mm, Color: ALL	V-0	
1.5 mm, Color: ALL	5VB V-0	
2.0 mm, Color: ALL	5VB V-0	
3.0 mm, Color: ALL	5VA V-0	

ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
0.75 mm, Color: ALL	V-0	
1.5 mm, Color: ALL	V-0	
2.0 mm, Color: ALL	V-0	

UL Solutions 的 Cookie
我们通过 Cookie 使内容和广告个性化，以便提供社交媒体功能并分析我们的流量。我们还与社交媒体、广告和分析合作伙伴来分享您使用网站的信息。 [了解更多](#)

Cookie 设置 拒绝全部 接受全部 Cookie

极速翻译

将当前网页翻译为:

极速引擎 更多专业引擎

引擎偏好设置

☐ 自动翻译此网站

2.0 mm, Color: ALL	5VB	
3.0 mm, Color: ALL	5VA	
Glow Wire Ignition Temperature (GWIT)		IEC 60695-2-13
0.75 mm	800 °C	
1.5 mm	800 °C	
2.0 mm	800 °C	
3.0 mm	800 °C	
Glow Wire Flammability Index (GWFI)		IEC 60695-2-12
0.75 mm	960 °C	
1.5 mm	960 °C	
2.0 mm	960 °C	
3.0 mm	960 °C	
ELECTRICAL PROPERTIES	VALUE	TEST METHOD
Hot-wire Ignition (HWI)		UL 746A
0.75 mm	PLC 3	
1.5 mm	PLC 3	
3.0 mm	PLC 1	
High Amp Arc Ignition (HAI)		UL 746A
0.75 mm	PLC 0	
1.5 mm	PLC 0	
3.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 3	UL 746A
Dielectric Strength	22 kV/mm	ASTM D149
UL Solutions 的 Cookie	1.0E+16 ohms-cm	ASTM D257/IEC 60093
我们通过 Cookie 使内容和广告个性化，以便提供社交媒体功能并分析我们的流量。我们还与社交媒体、广告和分析合作伙伴来分享您使用网站的信息。 了解更多		
THERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B

译

极速翻译

将当前网页翻译为:

极速引擎

更多专业引擎

引擎偏好设置

?

×

☐ 自动翻译此网站

2.0 mm	90 °C	
3.0 mm	90 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
0.75 mm	90 °C	
1.5 mm	90 °C	
2.0 mm	90 °C	
3.0 mm	90 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
0.75 mm	90 °C	
1.5 mm	90 °C	
2.0 mm	90 °C	
3.0 mm	90 °C	
Ball Pressure Temperature	75 °C	
PHYSICAL PROPERTIES	VALUE	TEST METHOD
Dimensional Change	0.040 %	ASTM D1042/ISO 2796
UV Exposure & Water Immersion	f2	UL 746C

Report Date: 1989-07-17

Revision Date: 2021-01-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

UL Solutions 的 Cookie

我们通过 Cookie 使内容和广告个性化，以便提供社交媒体功能并分析我们的流量。我们还与社交媒体、广告和分析合作伙伴来分享您使用网站的信息。[了解更多](#)