



df 22 8N (f1)

File Number: E507751

Yellow Card® 

COMPANY

Rohm GmbH
Deutsche-Telekom-Allee 9
Darmstadt, 64295 Germany

MODEL INFO

PLEXIGLAS® Satinice or ACRYLITE® Satinice: df 22 8N (f1)

Polymethyl Methacrylate (PMMA), light diffusing modified, furnished as pellets
(f1) – Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.
NOTE – In the US, EVONIK ROEHM GMBH uses the designation "ACRYLITE or ROHAGLAS" instead of "PLEXIGLAS". In China, EVONIK ROEHM GMBH uses the designation "PLEXIGLAS or ROHAGLAS" instead of "ACRYLITE".

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
1.5 mm, Color: NC	HB	
3.0 mm, Color: NC	HB	
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
1.5 mm, Color: NC	HB75	
3.0 mm, Color: NC	HB40	
Glow Wire Ignition Temperature (GWIT)		IEC 60695-2-13
1.5 mm	725 °C	
3.0 mm	750 °C	
Glow Wire Flammability Index (GWFI)		IEC 60695-2-12
1.5 mm	700 °C	

3.0 mm	725 °C	
ELECTRICAL PROPERTIES		TEST METHOD
Hot-wire Ignition (HWI)		UL 746A
1.5 mm	PLC 0	
3.0 mm	PLC 3	
THERMAL PROPERTIES		TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B
1.5 mm	90 °C	
3.0 mm	90 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
1.5 mm	90 °C	
3.0 mm	90 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
1.5 mm	90 °C	
3.0 mm	90 °C	
PHYSICAL PROPERTIES		TEST METHOD
UV Exposure & Water Immersion		UL 746C

Report Date: 2001-02-08

Revision Date: 2020-10-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"